

BExCP3-BG Break Glass Manual Call Point

The BExCP3-BG break glass manual call points are designed for the harshest of environments and approved for Zone 1, 2, 21 and 22 explosion proof hazardous areas for the control of fire and gas alarm systems. SIL2 compliant to IEC61508 (2010).

The BEx range features enclosures manufactured from corrosion proof, marine grade, copper free LM6 (A413) aluminium with a chromated and powder coat finish. Available with and without monitoring resistors all versions are certified to IECEx and ATEX standards with additional PESO, INMETRO and Ex EAC approvals. The break glass element features a safety membrane and is designed to snap ensuring the no glass fragments are released during activation. A hammer is available as an accessory if required by local code.

Features

- Alternative housing colours are available to meet specific requirements
- DIN rail mounted terminal blocks: 8 × 2.5mm²
- Optional stainless Steel lift flap
- Metalised Polyester or stainless steel duty label
- Series and/or End of Line resistors, diodes or Zener diodes
- Break glass hammer accessory available

Approvals

- ATEX certificate: Sira 09ATEX3286X
- IECEx certificate: IECEx SIR 09.0121X
- INMETRO certificate: 104Ex-0011X
- Ex EAC TR CU 012/2011 certified: KZ.1510019.22.01.00271
- SIL2 compliant to IEC 61508 (2010)
- PESO CCOE certified: P471504
- Complies with design requirements of EN54-11
- ECAS Ex 20-06-14792/E20-06-002576/NB0007

Coding

- BExCP3A-BG:
II 2G Ex db eb IIC T6 Gb Ta = -40°C to +70°C
II 2D Ex tb IIIC T75°C Db IP66
- BExCP3B-BG:
II 2G Ex db eb mb IIC T4 Gb Ta = -40°C to +50°C
II 2D Ex tb IIIC T60°C Db IP66
- BExCP3C-BG:
II 2G Ex db eb mb IIC T4 Gb Ta = -40°C to +65°C
II 2D Ex tb IIIC T75°C Db IP66



Specification

| | |
|------------------------------|---|
| BExCP3A-BG: | A version |
| Coding: | II 2G Ex db eb IIC T6 Gb Ta = -40°C to +70°C II 2D Ex tb IIIC T75°C Db IP66 |
| Switch rating: | 250V ac max. current 5.0A 250V dc max. current 0.25A 125V dc max. current 0.5A 75V dc max. current 0.75A 50V dc max. current 1.0A 30V dc max. current 5.0A max resistive, 3.0A inductive 12V dc max. current 5.0A |
| BExCP3B-BG: | B version |
| Coding: | II 2G Ex db eb mb IIC T4 Gb Ta = -40°C to +50°C II 2D Ex tb IIIC T60°C Db IP66 |
| Switch rating: | 48Vdc nom. 56Vdc max. 0.75A max. 24Vdc nom. 28Vdc max. 5.0A max. resistive, 3.0A inductive 12Vdc nom. 15Vdc max. 5.0A max. 6Vdc nom. 9Vdc max. 5.0A max. |
| Min. resistor (2W): | 48V = 1K8 24V = 470R 12V = 120R 6V = 47R |
| BExCP3C-BG: | C version |
| Coding: | II 2G Ex db eb mb IIC T4 Gb Ta = -40°C to +65°C II 2D Ex tb IIIC T75°C Db IP66 |
| Switch rating: | 125V dc max. current 0.5A resistive, 0.03A inductive 75V dc max. current 0.75A 48V dc max. current 1.0A 24V dc max. current 5.0A max resistive, 3.0A inductive 12V dc max. current 5.0A 6V dc max. current 5A |
| Min. resistor (1.5W): | 48V = 1K8 24V = 430R 12V = 110R 6V = 27R |
| Resistors (Current limited): | 48V < 1K8 max. current: 31mA 24V < 430R max. current = 62mA 12V < 110R max. current: 125mA 6V < 27R max. current = 250mA |
| General: | |
| Ambient: | Ta = -40°C to +70°C [-40° to +158°F] (+50°C for BExCP3B, +65°C for BExCP3C) |
| Switch: | Sealed - IP67 |
| Ingress protection: | IP66/67 |
| Enclosure material: | Marine grade copper free LM6 Aluminium |
| Enclosure finish: | Chromated & powder coated finish: anti-corrosion. |
| Colour: | RAL3000 Red (others available on request) |
| Cable entries: | 2 x M20 clearance top and 1 x M20 clearance side. Back box can be rotated to give 2 x bottom and 1 x side entries Adapters available to 1/2"NPT, 3/4"NPT or M25 |
| Stopping plugs: | 2 x Ex e nylon plugs as standard Brass, nickel plated brass and stainless steel Ex d plugs optional |
| Terminals: | 6 × 4.0mm ² cables or 8 × 2.5mm ² DIN rail |
| MTBF: | 1,079.94 years / 9,433,962 hours I- MIL 217 |
| Weight: | 0.8Kg |

Part Codes

| Version: | Part code variable: | Description: |
|--|---|---|
| Type: | BExCP3ABG BExCP3BBG BExCP3CBG | Type A: no EOL devices Ta -40°C to +70°C Type B: with EOL devices Ta -40°C to +50°C Type C: with EOL devices Ta -40°C to +65°C |
| Switch Type: [s] | S | SPCO/SPDT |
| Terminals: [t] | S D | 6 × 4mm ² terminals DIN Rail 8 × SAK2.5 [B or C version only] |
| Lift flap: [l] | L N | Lift flap No lift flap |
| Cable Entry Type: [e] | A B C D E F G | 3 × M20x1.5mm 2 × 1/2" NPT - adaptors 2 × 3/4" NPT - adaptors 2 × M25x1.5mm - adaptors 1 × 1/2" NPT - adaptor 1 × 3/4" NPT - adaptor 1 × M25x1.5mm - adaptor |
| Stopping plug material: [m] | B N P S | Brass Nylon Nickel Plated Brass Stainless Steel |
| Duty label / Equipment tag: [d]: | 1 2 3 4 5 6 7 | No Duty label, no Equip. tag Duty label Stainless Steel Duty label St/St + Equip. tag Duty label Metalised Polyester Duty label M. Poly. + Equip. tag Equip. tag only Special label requirement |
| Product version: [v]A | | IECEX, ATEX, EAC, INMETRO, PESO approved |
| Product options: [o] | 1 W | Standard product Alternative wiring option Config. 4 or 8 (B or C version only) |
| Enclosure colour: [x] | R B N Y V S K M Z | Red Blue Green Yellow Red/White Yellow/Black Black Magenta Red/Black |
| Default variable: [u] | N | Default = N - not currently used |
| Voltage: [v] | 48, 24, 12, 6 | System voltage Vdc (only required for BExCP3B or C type) |
| E.O.L.Module: [e] optional only for BExCP3B or C type | ExxxR ED1 ExxxZ | Resistor value in Ohms e.g. E470R = 470 Ohm Diode IN4007 = ED1 Zener diode e.g. E5V1Z = 5.1V |
| Series Module: [s] optional only for BExCP3B or C type | SxxxR SD1 SxxxZ | Resistor value in Ohms e.g. S1K5R = 1.5K Ohm Diode IN4007 = SD1 Zener diode e.g. S5V1Z = 5.1V |
| Spares: | SP70-0001 SP70-0040 | Replacement break glass elements (Pack of 50) BExCP3-BG Test Key |
| Accessories: | SP65-0001-A4 SP65-0002-A4 SP70-0065 | Pole Mount Bracket Kit 2" St/St A4 (316) Sunshade - St/St A4 (316) Break glass hammer with chain |

